



WTP-S03-1MGH

Frame:

Heavy-duty powder coated wraparound frame with 1-inch steel tubing | Rubber isolators to minimize vibration

Components:

Silicon carbide mechanical seals | Precision molded cast iron impeller and volute for reduced vibration and wear

Dependability is key when you need to remove unwanted water fast and efficiently. These compact, lightweight and portable 2-inch and 3-inch semi-trash pumps get the job done for homeowners, hobby farmers and contractors.

MODEL NUMBER	SUCTION DISCHARGE SIZE	MAX. TOTAL HEAD	SUCTION LIFT	DISPLACEMENT/ENGINE	PSI	MAX. CAPACITY	FUEL TANK CAPACITY	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-S02-1MGH	2in.x2in.	115ft.	28ft.	118cc Honda GX120 OHV	50	9,720 gph	0.53 gallon	20.5x17x16.25in.	71 lb.	62 lb.
WTP-S02-1MGM	2in.x2in.	115ft.	28ft.	212cc Mi-T-M OHV	50	9,720 gph	0.71 gallon	20.5x17x16.25in.	72 lb.	63 lb.
WTP-S03-1MGH	3in.x3in.	104ft.	28ft.	196cc Honda GX200 OHV	45	16,560 gph	0.83 gallon	21.25x17.25x18.25in.	82 lb.	73 lb.
WTP-S03-2MGM	3in.x3in.	104ft.	28ft.	212cc Mi-T-M OHV	45	16,560 gph	1.0 gallon	21.25x17.25x18.25in.	82 lb.	73 lb.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
15-0293	20-ft. x 2-in. green PVC hard suction hose with fittings	2-inch models
15-0295	50-ft. x 2-in. blue PVC soft discharge hose	2-inch models
19-0628	2-in. steel suction strainer with round openings	2-inch models
70-0524	2-in. suction and discharge kit	2-inch models
15-0294	20-ft. x 3-in. green PVC hard suction hose with fittings	3-inch models
15-0296	50-ft. x 3-in. blue PVC soft discharge hose	3-inch models
19-0629	3-in. steel suction strainer with round openings	3-inch models
70-0525	3-in. suction and discharge kit	3-inch models



2-inch suction and discharge kit, 70-0524

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov