



8-Gallon, 30-Gallon or Base-Mount

Air Compressor/ Generator Combinations

Two Stage — Gasoline



AG2-SV14-08M1

Ideal for jobsites and work trucks, the air compressor/generator combination units go a long way to increasing productivity. Install a stationary unit in your service truck and you'll have everything you need to operate air tools and power electrical tools.

Compressor Pump:

Cast iron compressor pump | Splash lubricated | Stainless-steel braided discharge hose | Large canister intake filter | Oil level sight indicator

Generator:

Brushless alternator | Total harmonic distortion (THD) less than 5% (6% on 30-gallon model) | 100% copper windings | (2) 120V, 20A and (1) 240V, 20A receptacles

Frame:

Powder coated 8-gallon or twin tank receivers (AG2-PV14-08M1 and AG2-SV14-08M1) | Powder coated ASME coded 30-gallon receiver tank (AG2-SV14-30M) | $\frac{3}{16}$ -inch base plate to reduce vibration | 16-gauge powder coated two-piece belt guard | 13-inch flat-free tires (AG2-PV14-08M1)

Components:

Regulator and two gauges for tank and outlet pressure | Manual drain valves for proper maintenance | $1\frac{1}{2}$ -inch fly wheel | Quality pilot valve unloader



30-Gallon Model

8-Gallon, 30-Gallon or Base-Mount Air Compressor/Generator Combinations – Two Stage – Gasoline

PORTABLE MODEL			ALTERNATOR WATTAGE			RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. AC OUTPUT	CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-PV14-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	408cc Vanguard OHV	Two stage	52x28x34in.	450 lb.	375 lb.

STATIONARY MODELS			ALTERNATOR WATTAGE			RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. AC OUTPUT	CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-SV14-08M1	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	408cc Vanguard OHV	Two stage	44x22x34in.	465 lb.	365 lb.
AG2-SV14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	408cc Vanguard OHV	Two stage	40x24.5x45in.	550 lb.	450 lb.

BASE-MOUNT MODEL			ALTERNATOR WATTAGE			RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. AC OUTPUT	CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-SV14-B	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	408cc Vanguard OHV	Two stage	47x22x28in.	390 lb.	325 lb.

*Equipped with 150-PSI maximum rated regulator.

Options:

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0028	Lifting hook - For easier portability	AG2-PV14-08M1 and AG2-SV14-08M1
AX-0063	Lifting hook - For easier portability	AG2-SV14-30M and AG2-SV14-B
AX-0070	Battery tray, box and 2-ft. of cables - Attaches to engine side of unit	AG2-SV14-30M
AX-0081	Electric start - battery, box and cables not included - For easy starting	All models
AX-0082	Electric start - battery box and cables included, battery not included - For easy starting	AG2-SV14-30M and AG2-SV14-B
IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use. Recommended for models mounted in service truck applications	AG2-SV14-30M

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
70-0358	Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy	All models
854-0093	Service truck mount kit - Includes four rubber isolators to reduce wear. Recommended for models mounted in service truck applications	AG2-PV14-08M1 and AG2-SV14-08M1
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	All models



NEMA 5-20R
120V



NEMA L6-20R
240V

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.