

### HDB Series — Belt Drive



HDB-3005-0K6G shown with wheel kit option, AW-5740-0014

*Perfect for agriculture and construction applications where mobility is a must, these compact skids are extremely portable and can fit through a 30-inch doorway. The versatility of this series makes it a popular choice for several industries.*

**Pump:**

Belt drive triplex piston General pump with ceramic plungers | Low pressure detergent injector

**Engine:**

Performance-proven gasoline engine or Kohler diesel engine with electric start – battery not included

**Frame:**

Powder coated steel square tube skid frame | Stainless-steel removable front panel | Optional wheel kit with locking tire brake, four tires and solid steel threaded axles

**Components:**

Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil | 12V Beckett burner – no need for a generator – battery not included | No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) | Adjustable thermostat

**Miscellaneous:**

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

**Unit Includes:**

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x 3/8-inch high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



# Skid Gasoline/Diesel

## Hot Water – HDB Series – Belt Drive

### Gasoline Models

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HDB-3004-OH6G	3000	3.9	389cc Honda GX390 OHV	1.7 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	685 lb.	566 lb.
HDB-3005-OV6G	3000	4.8	480cc Vanguard OHV	10.0 gallons	10.0 gallons	2.76 gph	386,400	53.5x28.75x42in.	720 lb.	601 lb.
HDB-3005-OK6G	3000	4.8	624cc Kohler CH620 OHV	10.0 gallons	10.0 gallons	2.76 gph	386,400	53.5x28.75x42in.	736 lb.	617 lb.

### Diesel Model

MODEL NUMBER	PSI	GPM	HORSEPOWER/ENGINE	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HDB-3004-OK7G	3000	3.9	9.1 HP Kohler KD440 OHV	1.3 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	745 lb.	626 lb.

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0156	<b>Hour meter</b> - Displays the number of hours unit has been in operation	All models
HX-0176	<b>Steam</b> - Increases outlet temperature to 250°F	HDB-3004 models
HX-0220	<b>High pressure chemical (K7)</b> - Adjustable high pressure chemical, includes float tank	All models
HX-0221*	<b>High pressure chemical (trapping unloader)</b> - Adjustable high pressure chemical, includes float tank	All models
HX-0222	<b>Panel engine key switch</b> - Moves engine key switch from engine to front panel	HDB-3005-OV6G
HX-0224	<b>Steam</b> - Increases outlet temperature to 250°F, includes steam nozzle and valve	HDB-3005 models
HX-0225	<b>Trapping unloader</b> - For hose runs longer than 50-feet and for cleaning elevated areas	All models
HX-0226	<b>Three-way ball valve</b> - Allows the pressure washer to be operated from garden hose, float tank, or trailer supply by adjusting ball lever valve	All models

**\*HX-0225 trapping unloader is required when ordering the HX-0221 high pressure chemical option.**

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0170	<b>Stack adapter</b> - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
850-0324	<b>Gasket (for 50-0170)</b> - Seals between 50-0170 stack adapter and boiler housing	All models
AW-5740-0014	<b>Wheel kit</b> - 4 rubber wheels allows unit to become portable	All models
AW-5740-0015	<b>Caster wheel kit</b> - Includes 2 caster wheels and 2 rubber wheels for easier movement on flat surfaces	All models
AW-6000-1007	<b>Hot water skid equipment cover</b> - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover	All models



**⚠ WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**